TerraPress G Silk

TYPICAL END USES	COLOUR PROFILE	FINISH	PRINTING METHODS
Magazines Brochures Leaflets	ECI_PSR_LWC_PLUS_V2.txt	Silk	Rotogravure

TECHNICAL DATASHEET (Target values)

Substance		**g/m²**	**60**
Brightness	D65/10°	%	83
Whiteness	CIE, ISO 11476, C2°	%	82
L*	D65/10°		91
a*	D65/10°		0.8
b*	D65/10°		-3.0
Opacity	D65/10°	%	92
Gloss Hunter	ISO 8254-1	%	43
Thickness	ISO 534	µm	51
Bulk	ISO 534	cm3/g	0.85
Smoothness	ISO 8791-4 PPS 1MPa	µm	0.8

Technical specifications are target values and may be subject to production variations.

REEL SPECIFICATIONS

Cores: 76 mm, 150 mm
Trimmed width: 7200 mm
Width: min. 388 mm, max. 4320 mm
Diameters: min. 1000 mm, max 1300 mm
Max. Weight: 10000 kg

ENVIRONMENT

Renewable fibre
Recyclable paper
Recyclable packaging materials
Sustainable sources

CERTIFICATES

EU Ecolabel
ISO 9001
ISO 14001
ISO 50001
OHSAS 18001
FSC® CoC
PEFC™ CoC

STORAGE AND HANDLING

- Store the paper in a humidity and temperature controlled area at 50 % relative humidity and room temperature between 19 °C and 23 °C.
- If the paper is stored in non - air conditioned warehouse, it is absolutely necessary to allow a stabilization period in the print room.
- Open the protective wrapping at the moment of use.

Kabel Premium Pulp & Paper GmbH
Schwerter Straße 263
58099 Hagen
Tel +49 (0) 2331 699-0
sales@k-premiumpaper.de

TerraPress G Gloss

TYPICAL END USES	COLOUR PROFILE	FINISH	PRINTING METHODS
Magazines Brochures Leaflets	ECI_PSR_LWC_PLUS_V2.txt	Gloss	Rotogravure

TECHNICAL DATASHEET (Target values)

Substance		**g/m²**	**57**	**60**
Brightness	D65/10°	%	82	82
Whiteness	CIE, ISO 11476, C2°	%	82	82
L*	D65/10°		91	91
a*	D65/10°		0.5	0.5
b*	D65/10°		-2.5	-2.5
Opacity	D65/10°	%	91	92
Gloss Hunter	ISO 8254-1	%	60	60
Thickness	ISO 534	µm	48	50
Bulk	ISO 534	cm3/g	0.84	0.83
Smoothness	ISO 8791-4 PPS 1MPa	µm	0.7	0.7

Technical specifications are target values and may be subject to production variations.

REEL SPECIFICATIONS

Cores: 76 mm, 150 mm
Trimmed width: 7200 mm
Width: min. 388 mm, max. 4320 mm
Diameters: min. 1000 mm, max 1300 mm
Max. Weight: 10000 kg

ENVIRONMENT

Renewable fibre
Recyclable paper
Recyclable packaging materials
Sustainable sources

CERTIFICATES

EU Ecolabel
ISO 9001
ISO 14001
ISO 50001
OHSAS 18001
FSC® CoC
PEFC™ CoC

STORAGE AND HANDLING

- Store the paper in a humidity and temperature controlled area at 50 % relative humidity and room temperature between 19 °C and 23 °C.
- If the paper is stored in non - air conditioned warehouse, it is absolutely necessary to allow a stabilization period in the print room.
- Open the protective wrapping at the moment of use.

Kabel Premium Pulp & Paper GmbH
Schwerter Straße 263
58099 Hagen
Tel +49 (0) 2331 699-0
sales@k-premiumpaper.de