

# Kabel Creamy Book 1.8

## TYPICAL END USES



Paperback

### CHARACTERISTICS

☑ Uncoated mechanical

### FINISH

☑ Machine finished

### PRINTING METHODS

☑ Offset  
☑ Flexo  
☑ Digital

## TECHNICAL DATASHEET (TARGET VALUES)

<b>Substance</b>	ISO 536	g/m <sup>2</sup>	<b>52</b>	<b>60</b>	<b>70</b>
<b>Thickness</b>	ISO 534	µm	94	110	126
<b>Volume</b>	ISO 534	cm <sup>3</sup> /g	1.8	1.8	1.8
<b>Brightness (D65/10°)</b>	ISO 2470-2	%	71	71	71
<b>L* (D65/10°)</b>	ISO 5631-2	%	91.5	91.5	91.5
<b>a* (D65/10°)</b>	ISO 5631-2	%	-0.2	-0.2	-0.2
<b>b* (D65/10°)</b>	ISO 5631-2	%	9.0	9.0	9.0
<b>Opacity</b>	ISO 2471	%	89	89	91

Technical specifications are target values and may be subject to production variations.



### ENVIRONMENT

Renewable fibre  
Recyclable paper  
Recyclable packaging materials  
Sustainable sources



### REEL SPECIFICATIONS\*

Cores: 76 mm, 150 mm  
Trimmed width: 7200 mm  
Width: min. 500 mm, max. 4320 mm  
Diameters: min. 1000 mm, max 1400 mm  
Max. Weight: 7000 kg

\* Different specifications on request only.



### CERTIFICATES

EU Ecolabel  
ISO 9001  
ISO 14001  
ISO 50001  
ISO 45001  
FSC® CoC  
PEFC™ CoC

## STORAGE AND HANDLING

- Store the paper in a humidity and temperature controlled area at 50% relative humidity and room temperature between 19°C and 23°C.
- If the paper is stored in a non - air conditioned warehouse, it is absolutely necessary to allow a stabilization period in the print room.
- Open the protective wrapping at the moment of use.



### Kabel Premium Pulp & Paper GmbH

Schwerter Straße 263  
58099 Hagen  
Tel +49 (0) 2331 699-0  
sales@kabelpaper.de



# Kabel Creamy Book 2.0

## TYPICAL END USES



Paperback

### CHARACTERISTICS

✔ Uncoated mechanical

### FINISH

✔ Machine finished

### PRINTING METHODS

✔ Offset  
✔ Flexo  
✔ Digital

## TECHNICAL DATASHEET (TARGET VALUES)

<b>Substance</b>	ISO 536	g/m <sup>2</sup>	<b>60</b>	<b>70</b>
<b>Thickness</b>	ISO 534	µm	120	140
<b>Volume</b>	ISO 534	cm <sup>3</sup> /g	2.0	2.0
<b>Brightness (D65/10°)</b>	ISO 2470-2	%	72	72
<b>L* (D65/10°)</b>	ISO 5631-2	%	91.5	91.5
<b>a* (D65/10°)</b>	ISO 5631-2	%	-0.2	-0.2
<b>b* (D65/10°)</b>	ISO 5631-2	%	9.0	9.0
<b>Opacity</b>	ISO 2471	%	89	91

Technical specifications are target values and may be subject to production variations.



### ENVIRONMENT

Renewable fibre  
Recyclable paper  
Recyclable packaging materials  
Sustainable sources



### REEL SPECIFICATIONS\*

Cores: 76 mm, 150 mm  
Trimmed width: 7200 mm  
Width: min. 500 mm, max. 4320 mm  
Diameters: min. 1000 mm, max 1400 mm  
Max. Weight: 7000 kg

\* Different specifications on request only.



### CERTIFICATES

EU Ecolabel  
ISO 9001  
ISO 14001  
ISO 50001  
ISO 45001  
FSC® CoC  
PEFC™ CoC

## STORAGE AND HANDLING

- Store the paper in a humidity and temperature controlled area at 50% relative humidity and room temperature between 19°C and 23°C.
- If the paper is stored in a non - air conditioned warehouse, it is absolutely necessary to allow a stabilization period in the print room.
- Open the protective wrapping at the moment of use.



### Kabel Premium Pulp & Paper GmbH

Schwerter Straße 263  
58099 Hagen  
Tel +49 (0) 2331 699-0  
sales@kabelpaper.de

