

Kabel Creamy Book 1.8

TYPICAL END USES



Paperback

CHARACTERISTICS

☑ Uncoated mechanical

FINISH

☑ Machine finished

PRINTING METHODS

☑ Offset

☑ Flexo

☑ Digital

TECHNICAL DATASHEET (TARGET VALUES)

Substance	ISO 536	g/m ²	60	70
Thickness	ISO 534	µm	110	126
Volume	ISO 534	cm ³ /g	1.8	1.8
Brightness (D65/10°)	ISO 2470-2	%	71	71
L* (D65/10°)	ISO 5631-2	%	91.5	91.5
a* (D65/10°)	ISO 5631-2	%	-0.2	-0.2
b* (D65/10°)	ISO 5631-2	%	9.0	9.0
Opacity	ISO 2471	%	89	91

Technical specifications are target values and may be subject to production variations.



ENVIRONMENT

Renewable fibre
Recyclable paper
Recyclable packaging materials
Sustainable sources



REEL SPECIFICATIONS*

Cores: 76 mm, 150 mm
Trimmed width: 7200 mm
Width: min. 500 mm, max. 4320 mm
Diameters: min. 1000 mm, max 1400 mm
Max. Weight: 7000 kg

* Different specifications on request only.



CERTIFICATES

EU Ecolabel
ISO 9001
ISO 14001
ISO 50001
ISO 45001
FSC® CoC
PEFC™ CoC

STORAGE AND HANDLING

- Store the paper in a humidity and temperature controlled area at 50% relative humidity and room temperature between 19°C and 23°C.
- If the paper is stored in a non - air conditioned warehouse, it is absolutely necessary to allow a stabilization period in the print room.
- Open the protective wrapping at the moment of use.



Kabel Premium Pulp & Paper GmbH

Schwerter Straße 263
58099 Hagen
Tel +49 (0) 2331 699-0
sales@kabelpaper.de



Kabel Creamy Book 2.0

TYPICAL END USES



Paperback

CHARACTERISTICS

☑ Uncoated mechanical

FINISH

☑ Machine finished

PRINTING METHODS

☑ Offset

☑ Flexo

☑ Digital

TECHNICAL DATASHEET (TARGET VALUES)

Substance	ISO 536	g/m ²	60	70
Thickness	ISO 534	µm	120	140
Volume	ISO 534	cm ³ /g	2.0	2.0
Brightness (D65/10°)	ISO 2470-2	%	72	72
L* (D65/10°)	ISO 5631-2	%	91.5	91.5
a* (D65/10°)	ISO 5631-2	%	-0.2	-0.2
b* (D65/10°)	ISO 5631-2	%	9.0	9.0
Opacity	ISO 2471	%	89	91

Technical specifications are target values and may be subject to production variations.



ENVIRONMENT

Renewable fibre
Recyclable paper
Recyclable packaging materials
Sustainable sources



REEL SPECIFICATIONS*

Cores: 76 mm, 150 mm
Trimmed width: 7200 mm
Width: min. 500 mm, max. 4320 mm
Diameters: min. 1000 mm, max 1400 mm
Max. Weight: 7000 kg

* Different specifications on request only.



CERTIFICATES

EU Ecolabel
ISO 9001
ISO 14001
ISO 50001
ISO 45001
FSC® CoC
PEFC™ CoC

STORAGE AND HANDLING

- Store the paper in a humidity and temperature controlled area at 50% relative humidity and room temperature between 19°C and 23°C.
- If the paper is stored in a non - air conditioned warehouse, it is absolutely necessary to allow a stabilization period in the print room.
- Open the protective wrapping at the moment of use.



Kabel Premium Pulp & Paper GmbH

Schwerter Straße 263
58099 Hagen
Tel +49 (0) 2331 699-0
sales@kabelpaper.de

